

DEC 10 2010

Searching PAJ

1/1 ページ

## PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2002-100767

(43)Date of publication of application : 05.04.2002

(51)Int.Cl.

H01L 29/78  
H01L 21/203  
H01L 21/316  
H01L 29/786

(21)Application number : 2000-290937

(71)Applicant : TOSHIBA CORP

(22)Date of filing : 25.09.2000

(72)Inventor : FUKUSHIMA SHIN  
SUGAWARA YUKIE  
YAMAGUCHI TAKESHI

## (54) SEMICONDUCTOR ELEMENT

## (57)Abstract:

PROBLEM TO BE SOLVED: To provide an MOS field effect transistor comprising a gate insulating film of high dielectric constant, while maintaining interface characteristics well maintained satisfactorily.

SOLUTION: An MOS field effect transistor comprises a semiconductor substrate (1), whose main component is Si and a gate insulating film (3) comprising a perovskite dielectrics, which is jointed directly on the semiconductor substrate for epitaxial growth. The lattice constant of the perovskite dielectrics is  $3.84 \text{ \AA}$ ;  $a < 3.88 \text{ \AA}$ . The perovskite dielectrics preferably comprises a composition represented by  $\text{Sr}_{1-x}\text{Ca}_x\text{Ti}_{1-y}\text{Zr}_y\text{O}_{3-d}$  ( $0.8 \leq x \leq 1.0$ ,  $0 \leq y \leq 0.5$ , while (d) represents oxygen deficiency and  $0 \leq d \leq 0.1$ ).

